

AFOSR-TR 970496

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE	3. REPORT TYPE AND DATES COVERED FINAL REPORT 01 Sep 95 - 28 Feb 97	
4. TITLE AND SUBTITLE (DURIP-95) Robust Quantum and Classical Cryptography for Security and Privacy in Photonic Imaging Network			5. FUNDING NUMBERS 61103D 3484/US	
6. AUTHOR(S) Professor Y. Fainman				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Univ of California, San Diego Dept of Electrical and Computer Engineering 9500 Gilman Drive La Jolla, CA 92093-0407			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NE 110 Duncan Avenue Suite B115 Bolling AFB DC 20332-8050			10. SPONSORING/MONITORING AGENCY REPORT NUMBER F49620-95-1-0478	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED			12b. DISTRIBUTION CODE	
<p>The acquired DURIP equipment was used to carry out the research in three projects as summarized below. Our research focussed on experimental realization and information theoretic analysis of quantum cryptosystems. We have introduced and, using the acquired equipment, conducted preliminary experiments on transmission of photon phase information employing frequency division technique suitable for practical realizations over free space or optical fiber network. The 2-3 order-of-magnitude mismatch between fiber and electronic device capacity can be used to increase the speed, reduce latency, increase security and reliability in the transmission and distribution of image information. To implement these applications, we used the equipment to construct an all-optical pre-processor at the transmitter and a post-processor at the receiver which performs multiplexing and demultiplexing, respectively. We have been investigating the diffractive optics with multifunctionality in polarization as well as programmable diffractive optics during the last five years employing natural birefringent and electrooptic nonlinear materials. Recently we initiated research into artificial dielectric materials (nanostructures) for photonic device applications. The acquired equipment also contributed to our characterization effort in the area of artificial dielectrics and diffractive optics.</p>				
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED			18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	
19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED			20. LIMITATION OF ABSTRACT	
			16. PRICE CODE	

Final Technical Report

for

**Defense University Research Instrumentation Program(95):
Robust Quantum and Classical Cryptography for
Security and Privacy in Photonic Imaging Network**

Sponsored by

Air Force Office of Scientific Research

Under Grant F-49620-95-1-0478

for Period 09/01/95 through 02/28/97

Grantee

The Regents Of the University of California, San Diego

University of California , San Diego

La Jolla CA 92093

Principal Investigators:

Y. Fainman

(619) 534-8909

Program Manager:

Dr. Alan Craig

(202) 767-4931

19971006 171

DTIC QUALITY INSPECTED 3

Acquired Equipment

1. MIRA 900F, Coherent Inc., modelocked titanium-sapphire source of femtosecond pulses and stabilized He-Ne laser from Spectra Physics Inc. (\$97 K).
2. Autocorrelator system from Inrad Inc., (\$16 K).
3. Detection systems Newport Corp. and FJW Optical System Inc. (9 K)
4. Oscilloscope from Tektronix, Power supplies from Glassman Inc. and HP (7 K)
5. High resolution and wide dynamic range CCD camera with interfaces TEA/CCD-1317K1 with controller, Princeton Instruments Inc. (20 K)
6. Optical table top and support system from Newport Inc. was required to be able installing the lasers (item#1) and set up research experiments (\$14 K)
7. High resolution optical spectrum analyzers WA-2500, PZ-91 and RG-93 programmable ramp generator from Burleigh Instruments Inc. (\$11 K)
8. Nonlinear $\chi^{(2)}$ and $\chi^{(3)}$ crystals (from Deltronic Crystals and CSK Optonics Corp.) with manipulators (from Newport Corp. and New Focus Inc.) (\$20 K)
9. SHG frequency doubler CSK Optonics Corp. (\$6 K)
10. High speed phase modulators SSA-128A-900 with SLM2256-128 from Meadowlark Optics Inc., and 10x10 with CTL256 from Displaytech (\$ 16 K)
11. Mirrors, lenses and manipulators from Oriel Inc. and Newport Inc. (\$ 6 K)
12. Data acquisition and laboratory controller from ATS Inc., Acropolis, etc. (\$ 17 K) to interface and control the electronic and electrooptic components of the experiments.

The total cost of the acquired DURIP(95) equipment was \$239 K consisting of \$199 K provided by the AFOSR DURIP(95) and the \$40 K matched by UCSD.

Projects Summary using Acquired Equipment

The acquired DURIP(95) equipment was used to carry out the research in three projects as summarized below.

Robust Quantum and Classical Cryptography for Security and Privacy in Photonic Imaging Network. (Y. Fainman, R. Rao, Y. T. Mazurenko, P. C. Sun, B. Slutsky, L. Shang)

Our research focussed on experimental realization [1-6] and information theoretic analysis of quantum cryptosystems [7-13]. On the theoretical side, we have studied the relationship between the secrecy capacity of a quantum cryptographic system and such factors as the error rate, line attenuation, and detector quality [7-9]. Quantum eavesdropping strategies and possible defenses against them were also investigated [10-13]. We have introduced and, using the acquired DURIP(1995) equipment, conducted preliminary experiments on transmission of photon phase information employing frequency division technique suitable for practical realizations over free space or optical fiber network [1-6]. The advantage of our technique is related to the fact that the phase difference between two signals spectrally separated by a small amount (in our experiments, 80 MHz) is not perceptibly affected by the physical stress to which the fiber carrying them may be subjected. Measurements were performed both with classical strength signals and with photomultipliers used as single photon detectors. Appropriate interfaces between the photomultipliers and the microcomputer controller was also established using the

DURIP(1995) grant. In a separate experiment, we also tested and verified that two signals with frequency separation of 80 MHz do not experience noticeable phase delay difference due to dispersion in a fiber under external temperature stress. We are currently investigating design and implementation of frequency-division long distance interferometer using all fiber components. We also continue our research on utilizing optical sources that obey sub-Poisson statistics using second order nonlinear optical crystals.

Our second approach uses classical encryption methods for privacy of next generation ultrahigh bandwidth photonic imaging networks. This work explores secure systems that make use of the large optical bandwidth of ultrashort pulses. The technique combines with optical code-division multiple access using stationary or dynamically varying time delays. We have demonstrated few components that are integral part of this system demonstration, including femtosecond laser pulse spectrum modulation using phase-only computer-generated-holograms [14], or a phase-only spatial light modulators. Each encrypted spectrum will be separated into two parts, and transmitted with an appropriately chosen delay between them. Coherent detection uses a complementary spectral-combining device combined with a sequence of temporal delays which allow the selection of the desired transmitter. The designated receiver will be able to compensate for the time-delay of the corresponding transmitter, combine the two complementary signals, and use the secure phase-decoder to decrypt the message. The coherent detection using three-wave mixing has been also demonstrated using the acquired DURIP(95) equipment [15-19]. The classical encryption system for photonic imaging network privacy employing spread spectrum techniques is currently constructed.

Optical Signal Processing with Femtosecond Pulses (Y. Fainman, Y. T. Mazurenko, P. C. Sun, K. Oba, and D. Marom)

The bandwidth and the efficiency of optical communication systems exceed these of electrical cable systems. Electronic devices and systems connected to optical networks may reach bit-rates on the order of 1-10 Gb/s. In contrast, the maximum bit-rate of a photonic network may exceed 1 Tb/s. The 2-3 order-of-magnitude mismatch between fiber and electronic device capacity can be used to increase the speed, reduce latency, increase security and reliability in the transmission and distribution of image information. To implement these applications, we used the acquired DURIP(95) equipment to construct an all-optical pre-processor at the transmitter and a post-processor at the receiver which performs multiplexing and demultiplexing, respectively [20-25]. The multiplexer performing image space-to-time transformation combines relatively slow but parallel in space electronic channels into an ultrahigh bandwidth serial optical channel (i.e., parallel-to-serial conversion), whereas the demultiplexer performs the inverse time-to-image space transformation for processing and/or electronic detection (i.e., serial-to-parallel conversion). For efficient bandwidth utilization, these processors need to be operated at rates determined by the bandwidth of the optical pulses [26]. Such space-time optical processors have been constructed using the equipment from this grant and applied for pulse shaping, filtering, and space-to-time multiplexing and time-to-space demultiplexing [20, 21, 27, 14-17].

Another example of using the acquired DURIP(95) equipment exploits applications that will benefit from an optical memory that will store and retrieve information in a format that is suitable for direct interface and transmission through an optical network, thereby, providing optimal performance in terms of hardware complexity, memory and network capacity, bandwidth, and latency. In this example we convert spatial image information into time domain. The corresponding data sequence in time is stored employing spectral domain 3-D volume holographic recording [18]. When the stored data is read out of the spectral domain storage system, the output spectrum is converted back into time sequence and sent through the all-optical fiber network to the user node. At the user node the time sequence is converted to

lower rate parallel channels in space domain for optical or electronic filtering and detection [17, 19].

In summary we introduced, analyzed and, using the acquired DURIP(95) equipment, evaluated experimentally a femtosecond pulse storage and imaging techniques useful for demultiplexing and parallel processing sequences of femtosecond pulses. Our pulse imaging method, based on 3-wave mixing in nonlinear crystals, allows converting complex amplitude of an ultrashort temporal pulse signal to a corresponding spatial image that resembles the temporal signal in space. Unlike the commonly used autocorrelator, our method carries both amplitude and phase information of the pulses. We also demonstrate nonvolatile storage of femtosecond pulses in photorefractive LiNbO₃ by recording and readout of spectral holograms at a wavelength of 460 nm and 920 nm, respectively. No degradation was observed after 24 hours readout. The demonstrated spectral domain nonvolatile holographic storage and the femtosecond pulse imaging are useful for broadband information systems applications.

Artificial dielectrics and diffractive optics with multifunctionality in polarization and color

(Y. Fainman, F. Xu, P. C. Sun, J. Thomas, R. Tyan, P. Shames, W. Nakagawa, P. Lin)

We have been investigating the diffractive optics with multifunctionality in polarization [28-32 and color [33-35] as well as programmable diffractive optics [36-43] during the last five years employing natural birefringent and electrooptic nonlinear materials. Recently we initiated research into artificial dielectric materials (nanostructures) for photonic device applications. The acquired DURIP(95) equipment also contributed to our characterization effort in the area of artificial dielectrics and diffractive optics. Modern microfabrication techniques (dry etching, electron beam lithography, patterned regrowth, epitaxial growth, laser assisted growth, laser ablation, etc.) allow to artificially fabricate sub-micron micro-structures which modify the dielectric and semiconductor properties such as birefringence, optical nonlinearity or optoelectronic interactions. For example, form birefringence or artificial birefringence effect occurs due to periodic microstructure boundary between two isotropic dielectric materials with different dielectric constants. The form birefringent microstructures possess several unique properties that make them superior compared to those of naturally birefringent materials: (i) high strength of form birefringence, $\Delta n/n$, can be obtained by selecting substrate dielectric materials with large refractive index difference (here Δn and n are the difference and the average effective indices of refraction for the two orthogonal polarizations, respectively), (ii) the magnitude of form birefringence, Δn , can be adjusted by varying the duty ratio as well as the shape of the microstructures, (iii) form birefringence can be constructed using an isotropic as well as anisotropic substrate, allowing to fine tune the anisotropic properties of naturally birefringent materials, and (iv) form birefringent microstructures can be used to modify the reflection properties of the dielectric boundaries. The artificial dielectric anisotropy due to form birefringence [44, 45] has been used to construct polarization optics components as well as polarization selective computer generated holograms [46, 47]. The form birefringence and the form birefringent computer generated holograms were characterized experimentally using the acquired DURIP(95) equipment.

We further extend this approach by designing a new device that uses unique properties of anisotropic spectral reflectivity (ASR) characteristics of a high spatial frequency multilayer binary grating [48, 49]. The ASR mechanism is based on combining the effects of the form birefringence of a high spatial frequency grating (i.e., grating period is much less than the wavelength of the incident field) with the resonant reflectivity of a multilayer structure. With our approach, the angular field and wavelength range have been largely increased compared to conventional polarization selective beam splitter (PBS) devices. The ASR PBS combine such unique features as compactness, compatibility with semiconductor materials, negligible insertion

losses, polarization selectivity for light at normal incidence, high polarization extinction ratios, and operation with waves of large angular bandwidth and from broad spectral range. Some interesting characteristics of the element with ASR characteristics cannot be found in a conventional PBS component. For instance, when our ASR device is designed to operate with normally incident light, it acts as a highly efficient polarization selective dielectric mirror [50-53]. The ASR devices have been fabricated and characterized using the acquired DURIP(95) equipment. Furthermore, our ASR device fabrication method is compatible with conventional microfabrication and can become easily integrable with other photonic devices such as VCSELs, MQW modulators, and photodetectors. Initial experiments with fabricated devices demonstrate good performance.

References

1. P. C. Sun, Y. Mazurenko and Y. Fainman "Long-distance frequency-division interferometer for communication and quantum cryptography," *Opt. Lett.*, **20**, 1062-1064, 1995
2. P. C. Sun, Y. Mazurenko and Y. Fainman "Transmission of optical phase information using frequency division of signals with application to quantum cryptography," *Sov. Optics and Spectroscopy*, v. **78**, #6, 1995
3. B. Slutsky, P. C. Sun, Y. Mazurenko, R. Rao, and Y. Fainman, " Long-distance frequency-division interferometer for communication and quantum cryptography," presented at the OSA Annual Meeting, Portland, September 1995.
4. B. Slutsky, P. C. Sun, Y. Mazurenko, R. Rao, and Y. Fainman, "Quantum cryptography for secret key generation using frequency-division long distance interferometry," presented at SPIE West'96, San Jose, 1996; also *Proc. SPIE*, 1996.
5. B. Slutsky, P. C. Sun, Y. Mazurenko, R. Rao, and Y. Fainman, "Quantum cryptography using frequency-division transmission of optical phase", *CLEO/Europe'96*, 1996
6. B. Slutsky and Y. Fainman, "Quantum cryptography uses photons to establish secret key," interview article in *OE Reports of SPIE, News and Commentary for the International Optical Engineering Community*, No. 147/March 1996.
7. B. Slutsky, P.C.Sun, Y.Mazurenko, R.Rao, and Y.Fainman, "Effect of channel imperfection on the secrecy capacity of a quantum cryptographic system," *J. of Modern Optics*, **44**, No. 5, 953-961, 1997.
8. B. Slutsky, P. C. Sun, Y. Mazurenko, R. Rao, and Y. Fainman, "Quantum Cryptography in the Presence of Noise and Losses" OSA Annual Meeting 1996, Rochester, New York
9. B. Slutsky, R. Rao, L. Tancevski, P. C. Sun, and Y. Fainman, " Information leakage estimates in quantum cryptography," presented at the *OSA Topical Meeting on Optics in Computing*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 115-117, March 1997.
10. B. Slutsky, R. Rao, L. Tancevski, P. C. Sun, and Y. Fainman, "Defense Against Bitwise Eavesdropping Strategies in Quantum Cryptography" OSA Annual Meeting 1996, Rochester, New York
11. L. Tancevski, B. Slutsky, R. Rao, Y. Fainman, " Evaluation of the cost of error correction protocol in quantum cryptographic transmission," submitted to *Proc. SPIE on Computer and Network Security Conference*, Dallas, Texas, November 1997.
12. B. Slutsky, R. Rao, Y. Fainman, " Security theorems in quantum cryptography," submitted to *Proc. SPIE on Computer and Network Security Conference*, Dallas, Texas, November 1997.

13. B. Slutsky, R. Rao, P. C. Sun, L. Tancevski, and Y. Fainman, "Defense Frontier Analysis of Quantum Cryptographic Systems", submitted to Applied Optics.
14. P. C. Sun, Y. T. Mazurenko, and Y. Fainman, "Real-time space/time processing with femtosecond laser pulses," presented at the SPIE's Annual Meeting, Denver, paper 2849-40, August 1996; Proc. SPIE, 1996 (invited paper)
15. P. C. Sun, Y. Mazurenko, Y. Fainman, "Femtosecond pulse imaging by nonlinear three-wave mixing," Proc. IEEE/LEOS, V. 2, p. 215, 9-th Annual Meeting of IEEE/LEOS, 1996
16. Y. Fainman, Y. Mazurenko, and P. C. Sun, "Ultra-fast Space-Time Processing," presented at the *OSA Topical Meeting on Optics in Computing*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 175-177, March 1997 (invited).
17. P. C. Sun, Y. Mazurenko, Y. Fainman, "Femtosecond pulse imaging: ultrafast optical oscilloscope," JOSA A, 14, 1159-1169, 1997
18. K. Oba, P. C. Sun, Y. Fainman, "Nonvolatile photorefractive spectral holography for time-domain storage of femtosecond pulses," CLEO'97, v. 11, 213-214, Baltimore, 1997.
19. Y. Fainman, Y. Mazurenko, and P. C. Sun, "Space-Time Optical Processing with Ultrafast Pulses," Proc. of Euro-American Workshop on Optical Pattern Recognition, 1997; also presented in the Euro-American Workshop on Optical Pattern Recognition, Barselona, Spain, 1-5 June, 1997 (Invited).
20. P. C. Sun, Y. Mazurenko, W. Chang, P. Yu and Y. Fainman " All-optical parallel-to-serial conversion by holographic spatial-to-temporal frequency encoding," Opt. Lett., 20, 1728-1730, 1995
21. P. C. Sun, Y. Mazurenko, and Y. Fainman, "All optical parallel-to-serial conversion by holographic spatial-to temporal requency encoding, OSA 1995 Topical Meeting on Optical Computing, Salt Lake City, Technical Digest, 1995
22. Y. Fainman, P.C. Sun, Y. Mazurenco, D. Brady, "Space-time processing with photorefractive volume holography," presented at the SPIE's 40-th Annual Meeting, San Diego, July 1995; Proc. SPIE, conf. 2529, 1995 (invited)
23. P. C. Sun and Y. Fainman, "Properties of holographic space-time signal processing," presented at the OSA Annual Meeting, Portland, September 1995.
24. D. Marom, P. C. Sun, Y. Fainman, "Temporal phase conjugation with space-time processors, " Holography," Vol.4, 1996 OSA Technical Digest Series, pp. 62-65, (OSA, Washington DC, 1996).
25. P. C. Sun, Y. Mazurenko, Y. Fainman, "Space-time processing of femtosecond optical pulses for imaging through fiber," OSA Annual Meeting 1996, Rochester, New York
26. Y. Fainman, " Optical Interconnections using broadband sources," *The First Workshop on Mutli-wavelength Free-Space Optoelectronic Interconnects*, Taos, NM, February 1996.
27. Y. Fainman, " Space-time processing with ultra-short laser pulses for holographic storage," International Symposium on Holographic Storage, Greece, May 1996 (invited paper).
28. F. Xu, J. Ford, and Y. Fainman, " Single-substrate birefringent computer-generated holograms," Opt. Lett., 21, 516-518, 1996
29. Y. Fainman, " Polarization selective computer generated holograms and applications, poster presented at the 1995 Gordon Conference on Optical Signal Processing and Holography, Plymouth, June 1995. (invited)
30. R. Tyan, F. Xu and Y. Fainman, " Characterization of birefringent computer generated holograms," presented at the OSA Annual Meeting, Portland, September 1995.

31. J. Ford and Y. Fainman, " Packaging Optics for Smart Pixels," presented at the *OSA Topical Meeting on Spatial Light Modulators*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 46-48, March 1997 (invited).
32. F. Xu, J. Ford, A. Krishnamoorthy, and Y. Fainman, " A 2-D VLSI/optoelectronic device packaged using a polarization selective computer generated hologram," presented at the *OSA Topical Meeting on Optics in Computing*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, PD3-1/PD3-4, March 1997 (Postdeadline paper).
33. J. Ford, F. Xu and Y. Fainman, " Wavelength-selective planar holograms," *Opt. Lett.*, **21**, 80-82, 1996
34. J. Ford, F. Xu and Y. Fainman "Color-selective planar gratings," presented at LEOS'95, San Francisco, November 1995.
35. F. Xu, R.-C. Tyan, J.E. Ford, and Y. Fainman, "Multiple order delay holograms for polarization and color selectivity," *Diffractive Optics and Micro-Optics*, Vol.5, 1996 OSA Technical Digest Series, pp. 356-359, (OSA, Washington DC, 1996).
36. J. Thomas and Y. Fainman "Programmable diffractive optical element using a multichannel PLZT phase modulator," *Opt. Lett.*, **20**, 1510-1512, 1995
37. J. Thomas and Y. Fainman, "Programmable diffractive optical element using a multi-channel PLZT phase modulator," presented at the OSA Annual Meeting, Portland, September 1995.
38. P. Shames and Y. Fainman, " Modeling of index of refraction variation in electro-optic materials with pattern electrodes," presented at the OSA Annual Meeting, Portland, September 1995.
39. P. Shames, P. C. Sun, Y. Fainman, "Modeling and optimization of electro-optic phase modulator," presented at SPIE West'96, San Jose, 1996; also *Proc. SPIE*, 1996.
40. P. Shames, P. C. Sun, Y. Fainman, "Modeling and characterization of PLZT-based array of polarization rotators," OSA Annual Meeting 1996, Rochester, New York
41. P. Shames, P. C. Sun, and Y. Fainman, "Empirically-based modeling for design of PLZT electro-optic devices," presented at the *OSA Topical Meeting on Spatial Light Modulators*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 168-170, March 1997.
42. J. Thomas and Y. Fainman, "A multistage arrangement for programmable diffractive optical elements providing simplified array control," presented at the *OSA Topical Meeting on Spatial Light Modulators*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 171-173, March 1997.
43. J. Thomas, M. Lasher, Y. Fainman, and Z. Parviz, "A PLZT-based dynamic diffractive optical element for high speed, random-access beam steering," to be presented at the SPIE's 1997 Annual Meeting, San Diego, 1997.
44. F. Xu, R. Tyan, P. C. Sun, C. Cheng, A. Scherer and Y. Fainman, " Form birefringence of periodic dielectric nanostructures," *Opt. Lett.*, **20**, 2457-2459, 1995
45. F. Xu, C. Cheng, A. Scherer, R. Tyan, P. C. Sun and Y. Fainman "Form birefringence of high-spatial frequency microstructures," presented at the OSA Annual Meeting, Portland, September 1995.
46. F. Xu, R. Tyan, , P. C. Sun, Y. Fainman, C. Cheng, A. Scherer, "Form-birefringent computer-generated holograms," *Opt. Lett.*, **21**, 1513-1515, 1996
47. F. Xu, R. Tyan, P. C. Sun, C. C. Chen, A. Scherer, and Y. Fainman, " Design of form birefringent computer-generated holograms," presented at the *OSA Topical Meeting on*

Optics in Computing, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 246-248, March 1997.

48. R. Tyan, P. C. Sun, A. Scherer and Y. Fainman, "Polarizing beam splitter based on the anisotropic spectral reflectivity characteristic of form-birefringent multilayer grating," *Opt. Lett.*, 21, 761-763, 1996
49. R. Tyan, P. C. Sun, Y. Fainman, "Polarizing beam splitters constructed of form-birefringent multilayer gratings," presented at SPIE West'96, San Jose, 1996; also *Proc. SPIE*, 1996.
50. R. Tyan, A. Salvekar, H. Chou, C. Cheng and A. Scherer, F. Xu, P. C. Sun and Y. Fainman, "Design, Fabrication and Characterization of Form-Birefringent Multilayer Polarizing Beam Splitter" *JOSA A*, 14, No 7, 1627-1636, 1997.
51. R. Tyan, A. Salvekar, C. Cheng, A. Scherer, P. C. Sun, F. Xu, Y. Fainman, "Characterization of polarizing beam splitter constructed of form-birefringent multilayer grating," *OSA Annual Meeting 1996*, Rochester, New York
52. Y. Fainman, "Artificial Dielectric Materials and Devices," *Workshop on Functional Mesooptics*, Crested Butte, Colorado, January 26-27, 1997.
53. R. C. Tyan, P. C. Sun, F. Xu, A. Salvekar, H. Chou, C. C. Cheng, A. Scherer and Y. Fainman, "Subwavelength multilayer binary grating design for implementing photonic crystals," presented at the *OSA Topical Meeting on Quantum Optoelectronics*, Incline Village, Lake Tahoe, Nevada, *Technical Digest*, p. 35-37, March 1997.